

Prelube 2000



KEY TECHNICAL PARAMETERS

Appearance: Slightly thickened, white liquid

Viscosity: 5000-15000 cps @10 rpm

pH: 6.5-8.0

Shelf life: 24 months

Temperature range: -5 up to 60

PRODUCT DESCRIPTION

Prelube 2000™ is a high-performance lubricant designed to coat the inner wall of a standard conduit prior to cable installation. This lubricant is proven to reduce frictional drag to increase installation speed, length, and safety in air-assisted installations. It is suitable for use with all types of communications cables and standard conduits and is available in quantities of 0.95, 3.8, and 18.9 litres.

APPLICATION AREA

Prelube 2000 is used to lubricate standard conduits in outdoor communications networks prior to cable installation.

DOSAGE DURING THE INSTALLATION

Conduit Size	Lubricant Quantity (per 1,000 m)
25/20 mm	300 ml
32/26 mm	400 ml
40/32 mm	500 ml
50/40 mm	600 ml
63/51 mm	800 ml

PRODUCT VARIATIONS

Product Name	Volume	MOQ / Packaging	SAP Code
Prelube 2000, 950 ml	950 ml	12	20095346
Prelube 2000, 3.8 l	3.8 l	4	20095344
Prelube 2000, 19 l	19 l	1	20095347