

House Lead-In Overground



PRODUCT DESCRIPTION

DuraHouse Lead-In Underground is designed for gas- and watertight sealing of a building entry point in FTTH applications. Suitable for use with up to 4 MicroDucts and cables.

APPLICATION AREA

For use with MicroDucts in above ground installations

MAIN CHARACTERISTICS

Material

Body:	Polycarbonate/Acrylonitrile styrene acrylate
-------	--

Temperature

Transport and storage:	-20 °C to +50 °C
Installation:	-20 °C to +50 °C
Operation:	-20 °C to +50 °C

Standards

Sealing:	DIN 18533
----------	-----------

Pressure

Burst:	2 bar for 24 hours
Working:	1 bar

Others

UV-Resistant:	Yes
Operational lifetime:	25 years

PRODUCT VARIATIONS

Material Description	Maximum Duct Diameter (mm)	Packaging (pcs)	SAP code
House Lead-In Overground 90° Multi 2 x 7 mm	2 x 7	6	20020391
House Lead-In Overground 90° Single 4-8 mm	4-8	25	20020092
House Lead-In Overground 90° Single 10-12 mm	10-12	1	20020093
House Lead-In Overground 90° Multi 1 x 10-12 mm / 2 x 7 mm	10-12	1	20020067