

Chamber 300x300mm



MAIN CHARACTERISTICS

Material

Body: PP

Covers: Concrete, Composite

Temperature

Installation: -45 °C to +95 °C

Operational: -45 °C to +95 °C

Others

UV resistant: No

Operational lifetime: 25+ years

Loading class of the body: D400

Loading class of the composite cover: B125

Loading class of the concrete cover: B125

N-force element: Not available

Standards

Accessories and cable management:
EN ISO 1461:2009

General: EN 124-1:2015

Manufacturing: EN ISO 9001

PRODUCT DESCRIPTION

Dura-Line Chamber is a preformed, structural underground access chamber for use in outdoor communications networks. It protects critical underground assets such as splice enclosures and slack loops of fiber optic cable and provides an access point for network installation and maintenance.


KEY ATTRIBUTES

- ▶ Available in sizes from 150 x 150 mm to 6 m in length
- ▶ Manufactured from 100% recycled polypropylene (PP) and is 100% recyclable
- ▶ Several cover options, including composite, ductile iron, and concrete

APPLICATION AREA


Dura-Line Chamber can be installed in grass verges, sidewalks/pavements, or roads/carriageway. Chambers have a preformed, structural design for easy on-site configuration and installation in 40 minutes or less. Chamber size differs according to location, fiber capacity requirements, and future network expansion needs. Component parts can be used interchangeably to adjust length, width, and height to build over existing ducts, or navigate unforeseen site obstacles. Duct entries, drainage, and chamber furniture (e.g., racks, steps) can be pre-fitted or fitted on site.

BODY OF CHAMBER TECHNICAL SPECIFICATIONS



Clear opening Width (mm)	300
Clear Opening Length (mm)	300
External Width (mm)	418
External Length (mm)	418
Section Depth (mm)	150
Total Depth (mm)	160
Weight (kg)	3.2

COVER OF CHAMBER TECHNICAL SPECIFICATIONS



Cover	Weight (kg)
Composite	7,5
Ductile Iron	20

PRODUCT VARIATIONS

Material Description	Dura-Line Part #
Chamber Composite cover/B 300x300 mm	20020484
Chamber Concrete infill cover/B 300x300 mm	20020485
Chamber segment 300x300x150 mm	20020486
Chamber segment 300x300x150 mm with floor	20020487

ORDERING INFO

To order a complete chamber, please choose:

- ▶ A cover made from your preferred material or requested loading class
- ▶ The number of segments based on the desired height of the chamber (1 segment is 150mm)
- ▶ If you require a chamber with a floor, choose "segment with floor" instead of one standard segment.